

# UL-TL30x6 Listed Composite Fire & Burglary

- UL TL-30×6 certified
  - UL certified Group 2M manipulation resistant combination lock with spy proof dial
  - Full composite construction comprised of the highest quality barrier material enclosed within heavy steel plates
  - Sophisticated glass relock system activates massive relockers when attacked
  - Bolts inter-lock within reinforced bolt chambers
  - Heavy plate steel frame
  - High quality adjustable hinges
  - **2 hours fire resistance**
- Custom interiors available



**2 HOUR**

*\*\* Specifications may not be exactly as listed*

Model Name	Interior			Exterior			Volume (ft. <sup>3</sup> )	Weight (lbs.)
	Height (in.)	Width (in.)	Depth (in.)	Height (in.)	Width (in.)	Depth (in.)		
TL30x6 2014	20	14 ½	15	28	22 ½	26	2.52	1323
TL30x6 2517	25	17 ½	15	33	25 ½	26	3.80	1685
TL30x6 3219	32	19 ½	17	40	27 ½	28	6.14	2221
TL30x6 4520	45	20 ½	21	53	28 ½	32	11.21	3240
TL30x6 5520	55	20 ½	21	63	28 ½	32	13.70	3716
TL30x6 6523	65	23	21	73	31	32	18.17	4512
TL30x6 6532	65	32	21	73	40	32	25.28	5474
TL30x6 7242	72	42	21	80	50	32	36.75	7095